

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Previously Presented) A device for impelling one or more liquids through an exit conduit comprising:

a housing having a chamber for receiving and/or holding one or more liquids under pressure and an exterior surface, and said housing having at least a first exit opening, a first inlet opening, a second exit opening, and a second inlet opening, each opening extending from said chamber to said exterior surface for receiving conduit means;

a first exit conduit means received by said first exit opening in communication with said chamber for transporting liquids from said chamber out of said first exit opening, said first exit conduit means for connection with an analytical device;

a first inlet conduit means received by said first inlet opening in communication said chamber for transporting a first liquid into said chamber, said first inlet conduit means for connection to a first supply device;

a second inlet conduit means received by said second inlet opening in communication with said chamber for transporting a second

liquid into said chamber, said second inlet means for connection with a second supply device;

a second exit conduit means received by said second exit opening in communication with said chamber for transporting liquids from said chamber out of said second exit opening, said second exit conduit means for connection with a waste receptacle;

at least one valve means disposed in at least one of said first exit conduit means, said second exit conduit means and said second inlet conduit means, said valve means having a closed position wherein liquid is prevented from flowing through said valve means and an open

position wherein said liquid is allowed to flow through said valve means, said valve means responsive to a signal to assume one of said positions; and

at least one fitting disposed between an opening and its associated conduit means, for forming a liquid-tight seal between said opening and associated conduit means and for retaining said associated conduit means in said opening when said pressure in said chamber is elevated,

wherein said chamber is for receiving liquid from each of said first inlet conduit means and said second inlet conduit means, and for discharging liquid through said first exit conduit means and said second exit conduit means, and

wherein said at least one fitting retains the associated conduit means in the opening at a chamber pressure between 15,000 psi and a maximum pressure of 120,000 psi.

2. (Original) The device of claim 1 wherein said at least one valve means is a freeze-thaw valve.

3. (Previously Presented) The device of claim 2 wherein said first liquid is a solute.

4. (Previously Presented) The device of claim 2 wherein said second liquid is a sample liquid.

5. (Original) The device of claim 1 further comprising a first exit conduit valve means interposed in said first exit conduit means.

6. (Original) The device of claim 5 wherein said first exit conduit means is a capillary having a first end in said first exit opening, a mid portion external to said housing, and a second end formed as a liquid chromatography column having an input end and an output end, wherein said first exit conduit valve means is disposed in said mid portion.

7. (Original) The device of claim 6 wherein said first end of said capillary extends into said chamber.

8. (Original) The device of claim 7 wherein a tip of said first end of said capillary is positioned in said chamber between said second inlet opening and said second exit opening.

9. (Original) The device of claim 6 wherein said capillary has an inner diameter between approximately 15  $\mu\text{m}$  and 150  $\mu\text{m}$ .

10. (Canceled)

11. (Previously Presented) The device of claim 1 further comprising a first supply device connected to said first inlet conduit means, said first supply device having a supply state wherein said first liquid is supplied at a pressure up to said maximum pressure and a stop state wherein said first liquid is not supplied, said first supply device responsive to a supply signal to assume one of said states.

12. (Original) The device of claim 11 further comprising a control means for controlling each of said at least one valve means by sending a signal to said valve means to assume one of said open and closed positions.

13. (Original) The device of claim 12 further comprising a control means for controlling a first supply device by sending a supply signal to said supply device to assume one of said supply and stop states.

14. (Original) The device of claim 13 wherein said control means sends a supply signal to said first supply device to effect a supply state of the first supply device and sends one or more signals to said at least one valve means to effect a closed position of all conduit valve means for filling and pressurizing said chamber.

15. (Previously Presented) The device of claim 13 wherein said control means sends a supply signal to said first supply device to effect a stop state of said first supply device and sends one or more signals to said at least one valve means to effect a closed position of said first exit conduit valve means and an open position of said second inlet conduit valve means and said second exit conduit means for replacing a liquid in said chamber with said second liquid.

16. (Previously Presented) The device of claim 13 further comprising a liquid monitor for monitoring a liquid passing through said second exit conduit means for providing said control means with information about the composition of the liquid exiting said chamber.

17. (Previously Presented) The device of claim 16 wherein said control means monitors said liquid at said second exit conduit for determining concentration.

18. (Previously Presented) The device of claim 13 wherein said control means sends a supply signal to said first supply device to effect a stop state of said first supply device and sends one or more signals to said at least one valve means to effect a closed position of said first exit valve means and said second inlet valve means and an open position of said second exit valve means for discharging liquid from said chamber.

19. (Previously Presented) The device of claim 13 wherein said control means sends a supply signal to said first supply device to effect a supply state of said first supply device and sends one or more signals to said at least one valve means to effect a closed position of said second inlet valve means and said second exit valve means and an open position of said first exit valve means for impelling a pressurized liquid through said first exit conduit means.

20. (Previously Presented) The device of claim 11 wherein said first supply device is a pump able to supply liquid against a pressure internal to said chamber up to said maximum pressure.

21. (Canceled)

22. (Original) The device of claim 20 wherein said pump is a binary pump capable of generating a gradient at said maximum pressure.

23. (Previously Presented) The device of claim 20 wherein said chamber is designed and constructed to hold liquids at pressures between approximately atmosphere and said maximum pressure.

24. (Canceled)

25. (Canceled)

26. (Canceled)

27. (Previously Presented) The device of claim 23 wherein said pressure in said chamber is between approximately 30,000 psi and 100,000 psi when liquid is impelled through said first exit opening.

28. (Original) The device of claim 1 further comprising a second exit conduit valve means interposed in said second exit conduit means.

29. (Original) The device of claim 1 further comprising a second inlet conduit valve means interposed in said second inlet conduit means.

30. (Previously Presented) The device of claim 1 further comprising a second liquid source connected to said second inlet conduit valve for supplying said second liquid.

31. (Canceled)

32. (Canceled)

33. (Previously Presented) The device of claim 1 further comprising: a vent opening in said housing extending from said chamber to said exterior surface for receiving a vent conduit means; and a vent conduit means received by said vent opening in communication with said chamber for transporting liquids from said chamber out of said vent opening, said vent conduit means for connection with a vent conduit valve means.

34. (Previously Presented) The device of claim 33 further comprising a vent conduit valve means interposed in said vent conduit means having an open position wherein liquid is allowed to flow through said vent conduit valve means and a closed position wherein liquid is prevented from flowing through said vent conduit valve means, and wherein said vent conduit valve means is responsive to a signal to assume one of said positions.

35. (Previously Presented) The device of claim 34 wherein said control means sends a supply signal to said first supply device to effect a stop state of said first supply device and sends one or more signals to said at least one valve means to effect a closed position of said first exit valve means and said second inlet conduit valve means and an open position for said second exit conduit valve means and said vent conduit valve means for discharging liquid from said chamber.

36. (Original) The device of claim 33 wherein said vent conduit means has an inner diameter between approximately 25  $\mu\text{m}$  and 150  $\mu\text{m}$ .

37. (Original) The device of claim 33 wherein said chamber has a cylindrical wall, a first end wall and a second end wall.

38. (Original) The device of claim 37 wherein said first inlet opening is positioned in one of the walls selected from said first and second end walls and said first exit opening is positioned in the other wall selected from said first and second end walls.

39. (Original) The device of claim 38 wherein said second inlet opening is positioned through said cylindrical wall proximate said first exit opening and said second exit opening is positioned through said cylindrical wall proximate said first inlet opening.

40. (Original) The device of claim 39 wherein said vent opening is positioned through said cylindrical wall approximately diametrically opposite said second input opening.

41. (Original) The device of claim 1 wherein said housing comprises an inert material.

42. (Original) The device of claim 41 wherein said inert material is stainless steel or titanium.

43. (Original) The device of claim 1 wherein said second inlet and second exit openings accommodate a conduit means having an inner diameter between approximately 15  $\mu\text{m}$  and 50  $\mu\text{m}$ .

44. (Previously Presented) A method for injecting one or more liquids into an exit conduit at high pressure comprising:

providing a housing having a chamber for receiving and/or holding one or more liquids under pressure and an exterior surface, and said housing having at least a first exit opening, a first inlet opening, a second exit opening, and a second inlet opening, each opening extending from said chamber to said exterior surface for receiving conduit means;

providing a first exit conduit means received by said first exit opening in communication with said chamber for transporting liquids from said chamber out of said first exit opening, said first exit conduit means for connection with an analytical device;

providing a first inlet conduit means received by said first inlet opening in communication said chamber for transporting a first liquid into said chamber, said first inlet conduit means for connection to a first supply device;

providing a second inlet conduit means received by said second inlet opening in communication with said chamber for transporting a second liquid into said chamber, said second inlet means for connection with a second supply device;

providing a second exit conduit means received by said second exit opening in communication with said chamber for transporting liquids from said chamber out of said second exit opening, said second exit conduit means for connection with a waste receptacle;

providing at least one valve means disposed in at least one of said first exit conduit means, said second exit conduit means and said second inlet conduit means, said valve means having a closed position wherein liquid is prevented from flowing through said valve means and an open position wherein said liquid is allowed to flow through said valve means, said valve means responsive to a signal to assume one of said open position and said closed position;

providing at least one fitting disposed between an opening and its associated conduit means, for forming a liquid -tight seal between said opening and associated conduit means and for retaining said associated conduit means in said opening when said pressure in said chamber is elevated; and

receiving a liquid from each of said first inlet conduit means and said second inlet conduit means; and discharging liquid through said first exit conduit means and said second exit conduit means,

wherein said at least one fitting retains the associated conduit means in the opening at a chamber pressure between 15,000 psi and a maximum pressure of 120,000 psi.

45. (Currently Amended) The method of claim 44 further comprising providing a first supply device connected to said first inlet conduit means, said first supply device having a supply state wherein said first liquid is supplied at a pressure up to a maximum pressure and a stop state



wherein said first liquid is not supplied, said first supply device responsive to a supply signal to assume one of said states.

46. (Previously Presented) The method of claim 45 further comprising providing a source of said second liquid in liquid communication with said second inlet conduit means.

47. (Original) The method of claim 46 further comprising providing a control means for controlling each of said at least one valve means by sending a signal to said valve means to assume one of said open and closed positions and for controlling a first supply device by sending a supply signal to said first supply device to assume one of said supply and stop states.

48. (Previously Presented) The method of claim 47 further comprising causing said control means to send one or more signals to said valve means and said first supply device to effect a sequence of positions and states for moving one or more liquids through said exit conduit means.

49. (Previously Presented) The method of claim 48 wherein said control means injects a quantity of said first liquid into said first exit conduit means by performing the actions comprising: a. sending a signal to all said conduit valve means to effect a closed state for sealing said chamber; b. sending a supply signal to said first supply device to effect a supply state for providing said first liquid and for raising a pressure of said first liquid to an impelling pressure in said chamber; and c. sending a signal to said first exit conduit valve means to effect an open position for injecting a quantity of said first liquid into said first exit conduit means.

50. (Previously Presented) The method of claim 48 wherein said control means injects said second liquid into said first exit conduit means by performing the actions comprising: a. sending a signal to said first exit conduit valve means to effect a closed position, sending a supply signal to said first supply device to effect a stop state and sending a signal to said second exit

conduit valve means to effect an open position, for reducing pressure in said chamber; b. when pressure in said chamber reaches a ambient pressure, sending a signal to said second inlet conduit valve means to effect an open position; c. feeding said second liquid into said chamber until said second liquid has displaced said first liquid; d. sending a signal to said second inlet conduit valve means and said second exit conduit valve means to effect a closed position, and sending a supply signal to said first supply device to effect a supply state to bring said pressure in said chamber to an impelling pressure; and e. maintaining said pressure in said chamber at said impelling pressure and sending a signal to said first exit conduit valve means to effect an open position for a predetermined time to inject said second liquid onto said first exit conduit means.

51. (Previously Presented) The method of claim 50 wherein said device further comprises a liquid monitor that monitors a liquid passing through said second exit conduit means for providing said control means information about the composition of said liquid exiting said chamber.

52. (Currently Amended) The method of claim 51 wherein step c is replaced by: feeding said second liquid into said chamber until said information from said liquid monitor indicates said second liquid has displaced said first liquid.

53. (Previously Presented) The method of claim 48 wherein said control means performs the actions comprising sending a signal to said first exit conduit valve means to effect a closed position and sending a signal to said second exit conduit valve means to effect an open position to reduce said pressure in said chamber and flush liquid from said chamber.

54. (Previously Presented) The method of claim 46 wherein said first liquid is a solute and said second liquid is a sample liquid.

55. (Original) The method of claim 45 wherein said first supply device is a pump.

56. (Original) The method of claim 44 wherein said first exit conduit means is a capillary.

57. (Previously Presented) The method of claim 48 wherein said device further comprises: a vent opening in said housing extending from said chamber to said exterior surface for receiving a vent conduit means; a vent conduit means received by said vent opening in communication with said chamber for transporting liquids from said chamber out of said vent opening; said vent conduit means for connection with a vent conduit valve means; and a vent conduit valve means interposed in said vent conduit means, said valve means having a closed position wherein liquid is prevented from flowing through said valve means and an open position wherein said liquid is allowed to flow through said valve means, said valve means responsive to a signal to assume one of said positions.

58. (Previously Presented) The method of claim 57 wherein said control means injects a quantity of said first liquid into said first exit conduit means by performing the actions comprising: a. sending a signal to all said conduit valve means to effect a closed state for sealing said chamber; b. sending a supply signal to said first supply device to effect a supply state for providing said first liquid and for raising a pressure of said first liquid to an impelling pressure in said housing; and c. sending a signal to said first exit conduit valve means to effect an open position for injecting a quantity of said first liquid into said first exit conduit means.

59. (Currently Amended) The method of claim 57 wherein said control means injects said second liquid into said first exit conduit means by performing the actions comprising: a. sending a signal to said first exit conduit valve means to effect a closed position, sending a supply signal to said first supply device to effect a stop state and sending a signal to said second exit conduit valve means and said vent conduit valve means to effect an open position, for reducing pressure in said housing; b. when pressure in said housing reaches a ambient pressure, sending a signal to said vent conduit valve means to effect a closed state and to said second inlet conduit

valve means to effect an open position; c. feeding said second liquid into said chamber until said second liquid has displaced said first liquid; d. sending a signal to said second inlet conduit valve means and said second exit conduit valve means to effect a closed position, and sending a supply signal to said first supply device to effect a supply state to bring said pressure in said chamber to said impelling pressure; and e. maintaining said pressure in said chamber at said impelling pressure and sending a signal to said first exit conduit valve means to effect an open position for a predetermined time to inject said second liquid onto said first exit conduit means.

60. (Previously Presented) The method of claim 57 wherein said control means performs the actions comprising sending a signal to said first exit conduit valve means to effect a closed position and sending a signal to said second exit conduit valve means and said vent conduit valve means to effect an open position to reduce said pressure in said housing and flush said second liquid from said chamber.

61. (Original) The method of claim 44 wherein said valves are freeze-thaw valves.